



Distributed by:



575 W HUME AVE
MUSKEGON, MI 49444
231.830.8070 | 800.726.4319
WWW.STARTEN.COM

STAR 10

PAINT STRIPPER THAT WORKS!



HOW to make your
home **BEAUTIFUL**
again!

REMOVING OLD FINISH TO BARE WOOD

- Step 1 Get an 8 oz sample
 - Step 2 Test a one square foot area
 - Step 3 Notice how it works
 - Step 4 Practice the technique before doing a large area
- Please call if you have any questions.

REMOVE: SIKKENS - TWP - HIGH SIERRA - SANSIN - POLYSEAL - NATUREONE - LINSEED OIL

ANY STAIN BY ANY MANUFACTURER

DOING YOUR PROJECT

1. Mask as necessary.
2. Apply Star 10 "Phase 1 Paste" at 70 square feet per gallon with a 1/2 gallon per minute airless paint sprayer using a .517 spray tip.
3. Clean your airless sprayer and tools with Star 10 "Phase 2 Liquid".
4. Let the "Phase 1 Paste" "dwell" for approximately two hours. The number of coats and different manufactures stain dictate the "dwell" time.
5. Remove the "Phase 1 Paste" by pressure washing with a 3,000 psi and three gallons per minute cold water unit. Use long sweeping strokes and over lap each stroke by 50%.

HINT: Two things most people do wrong is they do not apply the "Phase 1 Paste" thick enough and they do not let it "dwell" long enough.

Remove **1000** sq ft log face stain... with **TWO** men per day...

No Methylene Chloride, No Caustics, No Acids, No NMP



*Removed 5 coats of Sikkens stain, notice how clean the logs become.
NO damage to the log face and the **"fastest clean up"**
after stripping.*

Please check out our website, www.starten.com,
for a **how-to video** on log home stripping.